

DD112

**Dynamic hand
microphone
with one button**

Article-No.:
2208-002-000-02

**Product:****Characteristics**

- Dynamic microphone capsule
- Rugged chromed housing
- Durable PEIGUM® spiral cable
- Very long life switching contact

Options

- Splash protection for microphone capsule
- Protection against unintentional button presses
- Customized plugs and cables
- Special button colors or symbol
- Black matte housing

Application range

- Radio and PA systems in mobile and fixed applications

Accessories

- HV5 mount
- Rubber protective ring for microphone head
- Microphone preamplifier V966, V967, V856 and V857

Scope of delivery

- Hand microphone with PEIGUM® spiral cable

Technical Data:**General**

Housing:	Brass, brushed chrome
Dimensions:	Length 142 mm, Head Ø 29 mm, Body Ø 24 mm
Weight:	210 g (7.4 oz)
Connection:	4-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 1.5 m, without connector
Operating and display elements:	1 Button, black
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	150 Hz to 4 kHz at -10 dB
Sensitivity:	2 mV/Pa (-54 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Omnidirectional