

DD113

**Waterproofed,
dynamic
hand microphone
with three buttons**

Article-No.:
2208-034-000-03



Product:

Characteristics

- Waterproofed IP6K8
- Dynamic microphone capsule
- Rugged chromed housing
- Durable PEIGUM® spiral cable
- Protection against unintentional button presses
- Very long life switching contacts

Options

- Microphone preamplifier V966, V967, V856 and V857
- Customized plugs and cables
- Special button colors or symbols
- Black matte housing

Application range

- Radio and PA systems for mobile and fixed applications in harsh environmental conditions

Accessories

- HV5 mount
- Rubber protective ring for microphone head

Scope of delivery

- Hand microphone with PEIGUM® spiral cable
- Rubber protective ring for microphone head

Technical Data:

General

Housing:	Brass, sand blasted chrome (matte)
Dimensions:	Length 177 mm, Head Ø 33 mm, Body Ø 24 mm
Weight:	330 g (11.6 oz)
Connection:	6-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 2.5 m, without connector
Operating and display elements:	3 Buttons, green, orange, black
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	700 Hz to 4 kHz at -10 dB
Sensitivity:	4 mV/Pa (-48 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Omnidirectional