

DD113

**Waterproofed,
dynamic
hand microphone
with one button**

Article-No.:
2208-035-000-03



Product:

Characteristics

- Waterproofed IP6K8
- Dynamic microphone capsule
- Rugged chromed housing
- Durable PEIGUM® spiral cable
- Protection against unintentional button presses
- Very long life switching contact

Options

- Microphone preamplifier V966, V967, V856 and V857
- Customized plugs and cables
- Special button colors or symbols
- Black matte housing

Application range

- Radio and PA systems for mobile and fixed applications in harsh environmental conditions

Accessories

- HV5 mount
- Rubber protective ring for microphone head

Scope of delivery

- Hand microphone with PEIGUM® spiral cable
- Rubber protective ring for microphone head

Technical Data:

General

| | |
|---------------------------------|---|
| Housing: | Brass, sand blasted chrome (matte) |
| Dimensions: | Length 146 mm, Head Ø 33 mm, Body Ø 24 mm |
| Weight: | 275 g (9.7 oz) |
| Connection: | 4-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 2.5 m, without connector |
| Operating and display elements: | 1 Button, black |
| Storage temperature: | -30 °C to +70 °C (-22 °F to +158 °F) |
| Operation temperature: | -20 °C to +60 °C (-4 °F to +140 °F) |

Microphone

| | |
|------------------|-----------------------------|
| Frequency range: | 700 Hz to 4 kHz at -10 dB |
| Sensitivity: | 4 mV/Pa (-48 dBV/Pa ± 3 dB) |
| Impedance: | 200 Ω ± 20 % at 1 kHz |
| Directivity: | Omnidirectional |