

DD60

Dynamic hand
microphone
with one button

Article-No.:
2204-005-000-51



Product:

Characteristics

- Dynamic microphone capsule
- Rugged plastic housing
- Durable PEIGUM® spiral cable
- Easy to operate push to talk button

Options

- Customized plugs and cables
- Microphone preamplifier

Application range

- Radio and PA systems in mobile applications

Accessories

- HV7 mount
- HV13 mount
- HV21 mount

Scope of delivery

- Hand microphone with PEIGUM® spiral cable
- HV7 mount

Technical Data:

General

Housing:	Plastic PC-ABS, black
Dimensions:	Height 117 mm, Width 57 mm, Depth 29 mm
Weight:	160 g (5.6 oz)
Connection:	4-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 1.5 m, without connector
Operating and display elements:	1 Button, red
Storage temperature:	-40 °C to +70 °C (-40 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone

Frequency range:	180 Hz to 6 kHz at -10 dB
Sensitivity:	2 mV/Pa (-54 dBV/Pa ± 3 dB)
Impedance:	300 Ω ± 20 % at 1 kHz
Directivity:	Omnidirectional