

# DD60

**Electret hand  
microphone  
with one button**

Article-No.:  
**2204-011-000-51**



## Product:

### Characteristics

- Electret microphone capsule
- Unidirectional noise canceling
- Rugged plastic housing
- Durable PEIGUM® spiral cable
- Easy to operate push to talk button

### Options

- Level control
- Customized plugs and cables

### Application range

- Radio and PA systems in mobile applications

### Accessories

- HV7 mount
- HV13 mount
- HV21 mount

### Scope of delivery

- Hand microphone with PEIGUM® spiral cable
- HV7 mount

## Technical Data:

### General

Housing:	Plastic PC-ABS, black
Dimensions:	Height 117 mm, Width 57 mm, Depth 29 mm
Weight:	150 g (5.3 oz)
Connection:	4-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 1.5 m, without connector
Operating and display elements:	1 Button, red
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

### Microphone

Operating voltage:	1.5 V to 10 V
Frequency range:	100 Hz to 14 kHz at -10 dB
Sensitivity:	6 mV/Pa (-44 dBV/Pa ± 3 dB) at 5 V/2 kΩ
Impedance:	1.6 kΩ ± 20 % at 1 kHz/R <sub>L</sub> = 2 kΩ
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)