

TM67

Dynamic hand
microphone
with one button

Article-No.:
2102-017-000-03



Product:

Characteristics

- Dynamic microphone capsule
- Unidirectional noise canceling for close talking
- Rubber protective ring for microphone head
- Durable PEIGUM® spiral cable
- Very long life switching contact
- Protection against unintentional button presses

Options

- Customized plugs and cables
- Special button colors or symbols
- Black matte housing
- Microphone preamplifier V966, V967, V856 and V857

Application range

- Close talking in air traffic control and control centers

Accessories

- HV5 mount
- Windscreen WS16

Scope of delivery

- Hand microphone with PEIGUM® spiral cable
- Rubber protective ring for microphone head

Technical Data:

General

Housing:	Brass, sand blasted chrome (matte)
Dimensions:	Length 180 mm, Head Ø 29 mm, Body Ø 24 mm
Weight:	272 g (9.6 oz)
Connection:	4-wire halogen free PEIGUM® spiral cable, 2 Wires shielded, Draw length max. 2 m, without connector
Operating and display elements:	1 Button, orange
Storage temperature:	-25 °C to +70 °C (-13 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	300 Hz to 8 kHz at -10 dB
Sensitivity:	1.5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)