

# TM168

Dynamic  
microphone head

Article-No.:  
**2111-001-000-03**



## Product:

### Characteristics

- Dynamic microphone capsule
- Unidirectional high noise canceling
- Chromed housing
- Designed for gooseneck mounting

### Options

- Microphone preamplifier
- Black matte housing
- Mounted on gooseneck

### Application range

- Desktop microphones in indoor applications

### Accessories

- Various goosenecks and mounting brackets
- Windscreen WS16
- Microphone preamplifier V966, V967, V856 and V857

### Scope of delivery

- Microphone head with cable

## Technical Data:

### General

Housing: Brass, sand blasted chrome (matte)

Dimensions: Length 80 mm, Ø 24 mm

Weight: 120 g (4.2 oz)

Connection: 2-wire cable shielded, 1.8 m, without connector

Storage temperature: -30 °C to +70 °C (-22 °F to +158 °F)

Operation temperature: -20 °C to +60 °C (-4 °F to +140 °F)

### Microphone

Frequency range: 150 Hz to 12 kHz at -10 dB

Sensitivity: 1 mV/Pa (-60 dBV/Pa ± 3 dB)

Impedance: 200 Ω ± 20 % at 1 kHz

Directivity: Cardioid (at 1 kHz; 180° -20 dB)