

# TM169

## Dynamic microphone head

Article-No.:  
**2112-001-000-03**



### Product:

#### Characteristics

- Dynamic microphone capsule
- Unidirectional noise canceling
- Chromed housing
- Designed for gooseneck mounting

#### Options

- Microphone preamplifier
- Black matte housing
- Mounted on gooseneck

#### Application range

- Radio and PA systems in mobile and fixed applications

#### Accessories

- Various goosenecks and mounting brackets
- Microphone preamplifier V966, V967, V856 and V857

#### Scope of delivery

- Microphone head with cable

### Technical Data:

#### General

Housing:	Brass, sand blasted chrome (matte)
Dimensions:	Length 73.5 mm, Ø 29 mm
Weight:	140 g (4.9 oz)
Connection:	2-wire cable shielded, 1.8 m, without connector
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

#### Microphone

Frequency range:	50 Hz to 14 kHz at -10 dB
Sensitivity:	1.5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)