

TM2000

Dynamic twin
microphone head

Article-No.:
2116-001-000-03



Product:

Characteristics

- Two independent dynamic microphone capsules
- Unidirectional high noise canceling
- Chromed housing
- Designed for gooseneck mounting

Options

- Microphone preamplifier (max. 1 piece)
- Black matte housing
- Mounted on gooseneck

Application range

- Radio and PA systems in mobile applications
- Designed for use in large vehicles

Accessories

- Various goosenecks and mounting brackets

Scope of delivery

- Microphone head with cable

Technical Data:

General

Housing:	Brass, sand blasted chrome (matte)
Dimensions:	Length 124 mm, Ø 24 mm
Weight:	160 g (5.6 oz)
Connection:	2x 2-wire cable shielded, per 1.5 m, without connector
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone 1

Frequency range:	150 Hz to 12 kHz at -10 dB
Sensitivity:	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -20 dB)

Microphone 2

Frequency range:	150 Hz to 12 kHz at -10 dB
Sensitivity:	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -20 dB)