

ME352

**Electret
gooseneck microphone
with LED ring**

Article-No.:
2904-007-000-51



Product:

Characteristics

- Electret microphone capsule
- Unidirectional noise canceling
- Solid plastic housing with gooseneck
- Integrated windscreen
- LED ring

Options

- Customized plugs and cables
- Various lengths of goosenecks

Application range

- Radio and PA systems in fixed applications

Accessories

- Various mounting brackets for M10 screw thread
- Windscreen WS17

Scope of delivery

- Gooseneck microphone with cable

Technical Data:

General

Housing:	Plastic PC-ABS, black
Gooseneck:	Steel coil with external brass winding, black
Dimensions:	Length 335 mm, Head Ø 15 mm, Gooseneck Ø 10 mm
Weight:	110 g (3.9 oz)
Connection:	3-wires cable, shielded, 0.5 m, without connector
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone

Operating voltage (DC):	1.5 V to 9 V
Frequency range:	100 Hz to 12 kHz at -10 dB
Sensitivity:	8 mV/Pa (-42 dBV/Pa ± 3 dB) at 5 V/2 kΩ
Impedance:	1.6 kΩ ± 20 % at 1 kHz/R _L = 2 kΩ
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)

LED

Nominal current:	20 mA
Illuminance:	140 mcd
Series resistor:	Must be connected externally