

HA10

Handset with
thumb guard, one button
and cradle

Article-No.:
2506-025-000-51



Product:

Characteristics

- Dynamic ear and microphone capsules
- Large push-to-talk button
- Durable PEIGUM® spiral cable
- Cradle with locking mechanism for the handset with release button
- Automatic hook switch mechanism in the cradle
- Connection via screw-down terminal strip

Options

- Loudspeaker in the cradle
- Cradle with force release mechanism
- Flame resistant plastic housing
- Amplifier (built into in the A10 cradle)
- Electret microphone capsule

Application Range

- Radio and PA systems in mobile and fixed applications

Accessories

- Cradle loudspeaker 4 Ω
- Cradle loudspeaker 8 Ω

Scope of Delivery

- Handset with PEIGUM® spiral cable and cradle

Technical Data:

General

Housing:	Plastic PC-ABS, black
Dimensions with cradle:	Height 85 mm, Width 63 mm, Depth 213 mm
Weight:	395 g (13.9 oz)
Connection:	12 cond. terminal strip in the cradle, 6-wires halogen free PEIGUM® spiral cable, 2 wires shielded, Draw length max. 1.35 m
Operating and display elements:	1 button, orange release buttons, black
Storage temperature:	-30 °C to +70 °C (-13 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	200 Hz to 6 kHz at -10 dB
Sensitivity (in LRGP):	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Omnidirectional

Earpiece

Frequency range:	300 Hz to 4 kHz at -10 dB
Sensitivity:	26 dBPa/V ± 3 dB (IEC 3.2 Low-Leak coupler)
Impedance:	300 Ω ± 20 % at 1 kHz
Maximum output:	10 mW