

HA26

Handset with
one button

Article-No.:
2506-113-000-51



Product:

Characteristics

- Unidirectional noise canceling electret microphone capsule
- Dynamic ear capsule
- Solid plastic housing
- Durable PEIGUM® spiral cable
- Automatic hook switch mechanism (A12 cradle only)
- Large push-to-talk button

Options

- Customized plugs and cables
- Flame resistant plastic housing
- Amplifier
- Additional loudspeaker or hands-free microphone

Application Range

- Mobile radio and PA systems with increased ambient noise

Accessories

- A10 cradle
- A12, A12/2, A12/L cradle

Scope of Delivery

- Handset with PEIGUM® spiral cable

Technical Data:

General

Housing:	Plastic PC-ABS, black
Dimensions:	Height 41 mm, Width 58 mm, Depth 209 mm
Weight:	195 g (6.9 oz)
Connection:	7-wires halogen free PEIGUM® spiral cable, 1 wire shielded, Draw length max. 1.5 m, without connector
Operating and display elements:	1 button, orange
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone

Operating voltage (DC):	1.5 V to 10 V
Frequency range:	200 Hz to 14 kHz at -10 dB
Sensitivity (in LRGP):	2 mV/Pa (-54 dBV/Pa ± 3 dB) at 3 V/2 kΩ
Impedance:	1.4 kΩ ± 20 % at 1 kHz/R _L = 2 kΩ
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)

Earpiece

Frequency range:	300 Hz to 4 kHz at -10 dB
Sensitivity:	26 dBPa/V ± 3 dB (IEC 3.2 Low-Leak coupler)
Impedance:	300 Ω ± 20 % at 1 kHz
Maximum output:	10 mW