

HA26

**Handset with three
buttons for Sepura
SRM3500 and SRM3900**

Article-No.:
2506-198-000-51



Product:

Characteristics

- Unidirectional noise canceling electret microphone capsule
- Dynamic ear capsule
- Solid plastic housing
- Durable PEIGUM® spiral cable
- Automatic hook switch mechanism with A10 and A12 cradle
- Large push-to-talk button and two function buttons

Options

- Customized plugs and cables
- Flame resistant plastic housing

Application Range

- Mobile radio systems from Sepura (manufacturer)

Accessories

- A10, A12, A12/2, A12/L cradle
- Adapter cable for SEPURA SRM3500 and SRM3900 in various lengths

Scope of Delivery

- Handset with PEIGUM® spiral cable (Adapter cable is not included in the scope of delivery)

Technical Data:

General

Housing:	Plastic PC-ABS, black
Dimensions:	Height 41 mm, Width 58 mm, Depth 209 mm
Weight:	280 g (9.9 oz)
Connection:	9-wires halogen free PEIGUM® spiral cable, shielded, Draw length max. 1.5 m, plug RJ50 10 cond.
Operating and display elements:	3 buttons, orange (push-to-talk button), blue & yellow (function buttons)
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone

Operating voltage (DC):	1.5 V to 10 V
Frequency range:	200 Hz to 14 kHz at -10 dB
Sensitivity (in LRGP):	5 mV/Pa (-46 dBV/Pa ± 3 dB) at 3 V/2.2 kΩ
Impedance:	1 kΩ ± 20 % at 1 kHz/R _L = 2.2 kΩ
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)

Earpiece

Frequency range:	300 Hz to 4 kHz at -10 dB
Sensitivity:	26 dBPa/V ± 3 dB (IEC 3.2 Low-Leak coupler)
Impedance:	300 Ω ± 20 % at 1 kHz
Maximum output:	10 mW