

HA8

**Handset with
one push-to-talk button
ready for connection
on FuG 8/9**

Article-No.:
2506-186-001-51



Product:

Characteristics

- Dynamic ear capsule
- Electret microphone capsule
- Solid plastic housing
- Durable PUR spiral cable

Options

- Conductor RJ45 plug and adapter cable for terminal strip FuG 8/9

Application Range

- Analog public safety radio systems
- Installations with limited space

Accessories

- A8 cradle with screws

Scope of Delivery

- Handset with PUR spiral cable and plug U127/U
- A8 cradle with screws

Technical Data:

General

Housing:	Plastic PC-ABS, black
Dimensions with cradle:	Height 36.2 mm, Width 50 mm, Depth 160 mm
Weight:	190 g (6.7 oz)
Connection:	5-wires halogen free PUR spiral cable, 2 wires shielded, Draw length max. 1.5 m, plug U127/U
Operating and display elements:	1 push-to-talk button, blue
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone

Operating voltage (DC):	12 V
Frequency range:	150 Hz to 12 kHz at -10 dB
Sensitivity (in LRGP):	4 mV/Pa (-48 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Omnidirectional

Earpiece

Frequency range:	400 Hz to 4 kHz at -10 dB
Sensitivity:	17 dBPa/V ± 3 dB (IEC 3.2 Low-Leak coupler)
Impedance:	15 kΩ ± 20 % at 1 kHz
Max. input voltage:	500 mV