

TF13

**Water resistant
gooseneck
push-to-talk button**

Article-No.:
2703-045-000-51



Product:

Characteristics

- Rugged housing with gooseneck
- Integrated LED
- Protection class IP67
- Very long life switch contact

Options

- Customized plugs and cables

Application range

- Radio and PA systems in mobile and fixed applications
- Perfect for specialty vehicles under in harsh environmental conditions

Accessories

- BW2 Mounting bracket
- Dust cover

Scope of delivery

- Gooseneck push-to-talk button with cable
- Dust cover
- BW2 Mounting bracket

Technical Data:

General

Housing:	Plastic PA, black
Gooseneck:	Steel coil with external brass winding, black
Dimensions:	Length 365 mm, Head Ø 19 mm, Body Ø 15 mm, Gooseneck Ø 11 mm
Weight:	270 g (9.5 oz)
Connection:	4-wire cable, 2 wires shielded 3.6 m, without connector
Operating and display elements:	1 Button, blue 1 LED, red
Storage temperature:	-40 °C to +85 °C (-40 °F to +185 °F)
Operation temperature:	-30 °C to +70 °C (-22 °F to +158 °F)

Switch

Switching capacity:	max. 48 VDC/200 mA
Life cycle:	500,000
Protection class:	IP67
Operating force:	max. 3 N

LED

Nominal current:	20 mA
Illuminance:	Up to 125 mcd
Colour:	Red
Series resistor:	Must be connected externally